

## G.726-C62x Data Sheet

### Introduction

Beijing YiYuanZhuCheng (YYZC) G.726 voice coding software is an implementation of ITU Recommendation G.726 40, 32, 24, 16 kbit/s Adaptive Differential Pulse Code Modulation (ADPCM). The software runs on the Texas Instruments (TI) TMS320C62X family of Digital Signal Processors. Both encoder and decoder pass all ITU-T test vectors when reset function is called in the beginning. But the homing test is failed, since the original ITU C source code fails too.

### Resource Requirements<sup>\*†‡</sup>

Software	MCPS (Peak)	Algorithm Delay
Encoder	1.1	1 sample (0.125 ms)
Decoder	1.2	1 sample (0.125 ms)

Software	Program Memory	Const Data Memory	Scratch Memory	Stack Memory	Per Channel Data Memory
Encoder	4.1	0.3	0	0.1	0.05
Decoder	4.1	0.3	0	0.1	0.05
Encoder & Decoder	4.1	0.3	0	0.1	0.05

### Money Back Guarantee

We will return 50% license fees to our customers who find a better solution with 5% lower MIPS within one year of purchase. No other company in the world can guarantee this except us.

### Contact

Web: [www.yydsp.com](http://www.yydsp.com)

Email: [yyzdsp@gmail.com](mailto:yyzdsp@gmail.com)

\* All MCPS results are based on the worst case for any input and any bitrate. Only CPU cycles are counted.

† All memory usage figures are given in units of Kbyte.

‡ YYZC keeps the right to update the software without updating these figures.